

A **TATA** Product

VOLTAS

PROFIT FROM COOLING

COMMERCIAL REFRIGERATION RANGE 2021



ABOUT TATA GROUP

Founded in 1868, The Tata Group is a **global** business group with products and services in over **150** countries, over **706,511** employees and operations in over **100** countries. The group revenue is **\$110.7bn** with over **60%** generated in geographies other than India. The group is the **global leader** in several sectors.

VOLTAS



Voltas Limited is a premier air conditioning and engineering solutions provider and a projects specialist. Founded in India in 1954, Voltas Limited is part of the Tata Group, and in addition to Air Conditioners, Air Coolers, Water Dispensers, Water Coolers and Commercial Refrigeration products; Voltas offers smart engineering solutions for a wide spectrum of industries in areas such as heating, ventilation and air conditioning, refrigeration, electro-mechanical projects, electrification, textile machinery, mining and construction equipment, water management & treatment, cold chain solutions,

building management systems and indoor air quality. Voltas Limited is among the top 10 companies within the Tata Group and is the undisputed market leader in room Air Conditioners in India.

Since the launch, Voltas Commercial Refrigeration has been the undisputed leader in the cooling space. It offers a wide range of Commercial Refrigeration, Water Cooler and Water Dispenser products loaded with latest technology. The product range is thoughtfully made, keeping you and your business in mind and comes with features that boast of unmatched performance while being eco-friendly.



AIR COOLERS | AIR CONDITIONERS | AIR PURIFIERS | COMMERCIAL REFRIGERATORS | WATER COOLERS
WATER DISPENSERS | REFRIGERATOR | WASHING MACHINE | MICROWAVE OVEN | DISHWASHER

SMART FEATURES



Eco-friendly
Gas Refrigerant



UV Grade Plastic for
Long-Lasting Appearance



Spring Loaded Hinges
for Effortless Usage

< -25° C
0 to +10° C
Temperature Range



Energy Efficient
Compressor



Anti-Corrosive
Pre-Coated Body



Compact Design



Low-e
(Emission) Glass



Rugged and
Heavy-Duty Shelves



Dual Temperature
Freezing/Cooling



AUTO
Auto Defrost



LED
Led Light



Castor Wheels
for Easy Mobility



Stucco Aluminium /Metal
Inner Liner for Improved
Hygiene



Soft Aesthetic
Design



Single Mould
Construction



Tropicalized Machines



Upto 40% Electricity Saving



Longer Cooling Retention



Sunken Handles for
Safer Operations



Electronic Controller



Self Closing Door




Safety Compliant





HARD TOP CHEST FREEZERS



The Hard Top Chest Freezers are a great storage solution for ice-creams and frozen foods. The freezers are tropicalized for high temperatures. Excellent insulation helps maintain freezer temperatures even during power outages. Their corrosion-resistant durable bodies ensure reliability for years. Also, designed with an eco-friendly refrigerant and an energy-efficient compressor, they're great for the environment.




TECHNICAL SPECIFICATIONS - CHEST FREEZERS

Model No.	CF 120 SD HT	CF 205 SD HT	CF 320 SD HT	CF 320 DD HT	CF 405 DD HT	CF 500 DD HT	CF 600 DD HT
Product Dimension (WxDxH) in mm	670x565x830	834x665x830	1180x665x830	1180x665x830	1450x665x830	1680x665x830	1915x665x860
Gross Volume (In Ltr.)	120	205	320	320	405	500	600
No. Of Doors	1	1	1	2	2	2	3
Refrigerant Type	R-134a	R-134a	R-134a	R-134a	R-134a	R-134a	R-134a
Basket	1	1	1	1	2	2	2
Temperature Range	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C
PUF Thickness	60mm	60mm	60mm	60mm	60mm	60mm	60mm





HARD TOP CHEST COOLERS



Beverages should be chilled. Fruits and dairy products should always be fresh. Keeping them that way is the easiest with Hard Top Chest Coolers. Tropicalised for cooling in high ambient temperatures. A heavy compressor combined with a faster pull down time, chills the cabinet and the products almost instantly. sturdy in built. Designed for long term storage. Ideal for grocery stores, fast food outlets and restaurants.




TECHNICAL SPECIFICATIONS - CHEST COOLERS

Model No.	120 SD CC	205 SD CC	320 SD CC	320 DD CC	405 DD CC	500 DD CC
Product Dimension (WxDxH) in mm	670x565x830	834x665x830	1180x665x830	1180x665x830	1450x665x830	1680x665x830
Gross Volume (In Ltr.)	120	205	320	320	405	500
No. Of Doors	1	1	1	2	2	2
Refrigerant Type	R-134a	R-134a	R-134a	R-134a	R-134a	R-134a
Basket	1	1	1	1	2	2
Temperature Range	0° to 7°C	0° to 7°C	0° to 7°C	0° to 7°C	0° to 7°C	0° to 7°C
PUF Thickness	60mm	60mm	60mm	60mm	60mm	60mm



HARD TOP CONVERTIBLE



A marvel of cutting-edge technology in a corrosion-resistant durable body. Stores beverages, dairy products, frozen food and ice-cream alternative, at their ideal temperature. For innovative features like tropicalized compressor, multi-usage capabilities and cooking retention components, look no further. The storage system boasts of eco-friendly refrigerants which contribute to reduced global warming.

The Hard Top Convertibles are aesthetically crafted, and built to last for years to come.



TECHNICAL SPECIFICATIONS - CONVERTIBLES

Model No.	110 SD HT GREY CONVERTIBLE W	150 SD HT GREY CONVERTIBLE W	210 SD HT Grey Convertible W / 205 SD P HT CONVERTIBLE PCM	320 DD HT Grey Convertible W PCM / 320 DD HT P CONVERTIBLE PCM GREY	405 DD HT CONVERTIBLE PCM	500 DD HT CONVERTIBLE PCM	800 DD HT CONVERTIBLE
Product Dimension (WxDxH) in mm	620x550x830	735x575x826	925x575x826 / 834x665x830	1110x635x826 / 1180x665x830	1450x665x830	1680x665x830	1945X757X880
Gross Volume (In Ltr.)	110	150	210 / 205	320	405	500	800
No. Of Doors	1	1	1	2	2	2	2
Refrigerant Type	R-600a	R-600a	R-600a / R-134a	R-600a / R-134a	R-134a	R-134a	R-290a
Basket	1	1	1	1	2	2	1
Temperature Range	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)
PUF Thickness	70mm	70mm	65 mm / 60mm	65 mm / 60mm	60mm	60mm	70mm



COMBO COOLERS

METAL TOP



Enjoy the dual functionality of a cooler and a freezer, the cooler compartment can be used for storing cold beverages. The freezer, for storing ice-cream and frozen foods 'at the same time'. The coolers come with robust construction for heavy duty use.

Tropical compressor in Combo Coolers ensure high performance freezing even in higher ambient temperatures of the Indian summer.



TECHNICAL SPECIFICATIONS - COMBO COOLERS

Model No.	300 CB FC HT	400 CB FC HT
Product Dimension (WxDxH) in mm	1329X575X832 mm	1275X740X825 mm
Gross Volume (F/R) in litre	300	400
No. Of doors	2	2
Refrigerant Type	R600a	R290a
Basket	1	1
Temperature Range	<-18°C(Freezer), 0° to 7°C(Cooler)	<-18°C(Freezer), 0° to 7°C(Cooler)
PUF thickness	65 mm	70 mm



Soft Aesthetic Design



Castor Wheels For Easy Mobility



Energy Efficient Compressor



Upto 40% Electricity Saving



Stucco Aluminium /metal Inner Liner For Improved Hygiene



UV Grade Plastic For Long-lasting Appearance



Door Lock For Restricted Accessibility



Anti-corrosive Pre-coated Body



Spring Loaded Hinges For Effortless Usage



Eco-Friendly Gas Refrigerant



Compact Design



Safety Compliant



Tropicalized Machines



Dual Temperature Freezing/cooling



FLAT GLASS TOP FREEZERS



Frozen foods and ice creams find a robust and reliable home in the Flat Glass Top Freezers to showcase the products more prominently. Built sturdy for heavy use. Freezers are tropicalised for better cooling at higher temperatures. Low-emissive glass for better visibility and insulation. Also available with an optional in-built stabilizer and LED lights.



- Soft Aesthetic Design
- Castor Wheels For Easy Mobility
- Energy Efficient Compressor
- Upto 40% Electricity Saving
- Rugged And Heavy-duty Shelves
- UV Grade Plastic For Long-lasting Appearance
- Door Lock For Restricted Accessibility
- Anti-corrosive Pre-coated Body
- Longer Cooling Retention
- Low Emissivity Glass To Avoid Cooling Loss
- Compact Design
- Safety Compliant
- Tropicalized Machines
- Stucco Aluminium /metal Inner Liner For Improved Hygiene
- Eco-Friendly Refrigerant

TECHNICAL SPECIFICATIONS - FLAT GLASS TOP FREEZERS

Model No.	50 GSL	120 GSL	205 GSL / 210 FGSL	320 GSL	405 GSL
Product Dimension [WxDxH] in mm	620X540X500	685x535x815	848X635X815/ 930x545x784	1195X635X815	1465X635X815
Gross Volume (In Ltr.)	50	120	205 / 210	320	405
No. Of Doors	2	2	2	2	2
Refrigerant Type	R-134a	R-134a	R-134a /R600a	R-134a	R-134a
Basket	1	1	1	1	2
Temperature Range	<-18°C	<-18°C	<-18°C	<-18°C	<-18°C
PUF Thickness	60mm	60mm	60mm / 65mm	60mm	60mm



CURVED GLASS TOP FREEZERS



Showcase in style. Ideal for the storage and display of ice-creams and frozen foods. Castor wheels at the bottom offer easy mobility.



TECHNICAL SPECIFICATIONS - CURVED GLASS TOP FREEZERS

Model Name	150 Curved Glass Top Freezer	300 Curved Glass Top Freezer	400 Curved Glass Top Freezer
Product Dimension (WxDxH) in mm	770x606x842	1095x606x842	1425x606x842
Gross Volume (In Ltr.)	165	300	400
No.Of Doors	2	2	2
Refrigerant Type	R 290a	R 290a	R134a
Basket/Shelves	1-QDI	2-QDI	2-QDI
Temperature Range	≤-18°C	≤-18°C	≤-18°C
PUF Thickness	75 mm	75 mm	76 mm





CHOCOLATE COOLERS



What could make chocolates look even better? The Chocolate Coolers.

Combining sturdy with style, their polished design showcases the chocolates in the best way possible.

The coolers are tropicalised to maintain the optimum temperature under high ambient temperatures. The shelves are customisable. It even comes with LED lights to shine the spotlight on your star products.



-  Single Mould Construction
-  Led Light
-  Stucco Aluminium /metal Inner Liner For Improved Hygiene
-  Safety Compliant
-  Uv Grade Plastic For Long-lasting Appearance
-  Anti-corrosive Pre-coated Body
-  Tropicalized Machines
-  Low Emissivity Glass To Avoid Cooling Loss
-  Compact Design
-  Energy Efficient Compressor
-  Soft Aesthetic Design

TECHNICAL SPECIFICATIONS -CHOCOLATE COOLERS

Model No.	CT 15	CT 33
Product Dimension(mm)	440X600X450	610X538X450
Gross Volume (In Ltr.)	15	30
No.Of Glass Doors	1	1
Refrigerant Type	R134 a	R134 a
Basket/Shelves	Yes Customized	Yes Customized
Temperature Range	+18 to +22°C	+18 to +22°C
PUF Thickness	40 mm	40 mm



VISI COOLERS



Form meets function in this stylish merchandiser. The Visi Coolers are especially designed to cool uniformly as well as showcase the products inside. Ideal for storing beverages and dairy products for a longer time at desired temperatures. The low emissivity glass is there for more than just good looks. It also restricts the loss of cooling. The coolers are tropicalized for cooling in high temperatures and designed for faster pull down time. They also come with an option for in-built stabilizer and LED lights. These compact storage solutions are a perfect match for commercial cooling purposes.



- Soft Aesthetic Design
- Castor Wheels For Easy Mobility
- Led Light
- Upto 40% Electricity Saving
- Rugged And Heavy-duty Shelves
- UV Grade Plastic For Long-lasting Appearance
- Anti-corrosive Pre-coated Body
- Longer Cooling Retention
- Low Emissivity Glass To Avoid Cooling Loss
- Compact Design
- Energy Efficient Compressor
- Safety Compliant
- Tropicalized Machines
- Self Closing Door

TECHNICAL SPECIFICATIONS - VISI COOLERS

Model No.	VC 70	VC 120	VC 220	VC 320	VC 425
Product Dimension	455 x 515 x 720	475 x 585 x 1060	535 x 670 x 1405	560 x 705x 1700	650 x 640 x 1960
Gross Volume [In Ltr.]	70	120	220	320	425
No.Of Doors	1	1	1	1	1
Refrigerant Type	R-134a	R-134a	R-134a	R-134a	R-134a
Basket/Shelves	2	2	3	4	4
Temperature Range	0°C to 7°C	0°C to 7°C	0°C to 7°C	0°C to 7°C	0°C to 7°C
PUF Thickness	45mm	45mm	45mm	45mm	45mm

FREEZER ON WHEELS



Store your ice cream for longer. Move it with the utmost ease with Freezer on Wheels. These freezers come with sturdy anti-corrosive plastic mould bodies that offer a longer life to your products. Tropicalized compressors provide better cooling. Attractive colour options offer better product display. A sturdy design allows better temperature retention. Sturdy wheels allow ease of movement.



Safety
Compliant



Easy Accessibility



Single Mould
Construction



Anti-corrosive
Pre-coated Body



Longer Cooling
Retention.



Tropicalized
Machines



Compact Design



Energy Efficient
Compressor

TECHNICAL SPECIFICATIONS-FREEZER ON WHEELS

Model No.	VFOWE HT 100 SD	VFOWE HT 135 SD S	VFOWE HT 135 DD S
Product Dimension(mm)	940 X 635 X 695mm	940 X 635 X 795mm	940 X 635 X 795mm
Net Volume (In Ltr.)	100	135	135
No.Of Doors	1	1	2
Refrigerant Type	R404a	R404a	R404a
Temperature Range	-18 to -30 °C	-18 to -30 °C	-18 to -30 °C
PUF Thickness	65mm	65mm	65mm

WATER COOLERS

STAINLESS
STEEL TOP



Quench your thirst for chilled water with Voltas Water Coolers. A Stainless Steel 304 and reciprocating tropicalized compressor, housed in a vertical design for near-instant optimum cooling. Never run out of cool water again.



TECHNICAL SPECIFICATIONS - WATER COOLER

Model	20/20 PSS & FSS	20/40 PSS & FSS	40/40 PSS & FSS	40/80 PSS & FSS	60/80 PSS & FSS	60/120 PSS & FSS	150/150 PSS & FSS-Recip./ Rotary Compressor	150/300 PSS & FSS
Storage Capacity (Ltrs)	20	40	40	80	80	120	150	300
Cooling Capacity (Ltrs/hour)	20	20	40	40	60	60	150	150
Cabinet Material	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS
Storage Tank Material	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Number Of Fucets	1	1	2	2	2	2	2	5 [3+2 OPTIONAL]
Compressor	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A
Temperature Range	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C
Refrigerant	R- 134 a	R- 134 a	R - 134a	R-134a	R-134a	R-134a	R - 22	R - 134a
Over All Product Dimensions With Trough (Wxdxh) Mm	364 X 505 X 1117	461 X 582 X 1217	461 X 582 X 1217	461 X 582 X 1441	461 X 582 X 1441	564 X 705 X 1397	564 X 705 X 1521	1250x890x1500

SPECIALIZED WATER COOLERS

Model	20/40 PSS & FSS-NCW	40/80 PSS & FSS-NCW	40/80 PSS & FSS-UV	40/80 PSS & FSS-UV+NCW	60/120 PSS & FSS-UV	150/150 PSS & FSS-UV
Storage Capacity (Ltrs)	40	80	80	80	120	150
Cooling Capacity (Ltrs/hour)	20	40	40	40	60	150
Cabinet Material	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS	PCM / SS
Storage Tank Material	SS 304	SS 304	SS 304	SS 304	SS 304	SS 304
Number Of Fucets	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2=1+1 [1 NORMAL+1 COLD]	2	2
Compressor	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R134A	RECIP.-R22A
Temperature Range	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C	8 TO 24 ° C
Refrigerant	R- 134 a	R-134a	R-134a	R-134a	R-134a	R - 22
Over All Product Dimensions With Trough (Wxdxh) Mm	461 X 582 X 1217	461 X 582 X 1441	461 X 582 X 1441	461 X 582 X 1441	564 X 705 X 1397	564 X 705 X 1521

Note:- * R-134a gas will be available in Selected models for GEMS



Soft Aesthetic Design



Longer Cooling Retention.



Compact Design



Safety Compliant



Upto 40% Electricity Saving



Eco-Friendly Gas Refrigerant



Anti-corrosive Pre-coated Body



Energy Efficient Compressor




Tropicalized Machines



In-situ Puf Insulation



WATER DISPENSERS



Not just hot and cold but also pure and safe.

Presenting the new range of water dispensers with RO purifiers. The new range does more than let you choose between Hot, Normal & Cold water. It also puts every drop through a 4-stage filtration process. A Sediment filter, Pre-carbon filter, RO membrane and Post-carbon filter.

Water Dispensers are the smart choice for every office and home.



Soft Aesthetic Design



UV Grade Plastic For Long-lasting Appearance



Eco-Friendly Gas Refrigerant



Energy Efficient Compressor



Safety Compliant



Tropicalized Machines



Compact Design



Anti-corrosive Pre-coated Body

TECHNICAL SPECIFICATIONS - WATER DISPENSERS

Model	Minimagic Pure T	Minimagic Pure R	Minimagic Pure F	Minimagic Pearl R BLACK / RED	Minimagic Pure F W/O Cabinet	Minimagic SPRING R	Minimagic Super T	Minimagic Super R
Type	Table Top	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Table Top	Floor Mounted
Cabinet Type	NA	Cooling Cabinet	only storage cabinet	Cooling Cabinet	NA	Cooling Cabinet	NA	Cooling Cabinet
No. of Faucets	3	3	3	3	3	3	3	3
Cold Water Storage Capacity (Ltrs)	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
Cooling Capacity (Ltrs/Hr)	3	2.5	3	2.5	3	3	3	2.5
Hot Water Storage Capacity (Ltrs)	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Unit Dimension (W X D X H) in mm	310 x 345 x 490	310 x 345 x 940	310 x 345 x 940	310 x 345 x 940	310 x 345 x 940	310 x 330 x 970	325x380x555	325x380x1000
Weight in Kg.	12.8	18.2	16.7	18.2	16.7	16.5	11.4	16.5
Refrigerant	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	NA	20 Ltrs	20 Ltrs	20 Ltrs	NA	15 Ltrs	N/A	19/20
Cooling Cabinet Temperature	NA	≤12°C	NA	≤12°C	NA	≤12°C	NA	≤12°C
Tap Function	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold
Display	LED Indicator	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	Led Indicator	LED Indicators
RO TDS	NA	NA	NA	NA	NA	NA	NA	NA

Model	Minimagic Super F	Minimagic Wave T	Minimagic Wave R	Minimagic Wave F	Minimagic FM BL 3 V Pure	Voltas Minimagic WDR FM 3 V Pure RO	Voltas Minimagic WDR TT 2 V Pure RO
Type	Floor Mounted	Table Top	Floor Mounted	Floor Mounted	Floor Mounted	Floor Mounted	Table Top
Cabinet Type	only storage cabinet	NA	Cooling Cabinet	only storage cabinet	only storage cabinet	RO Kit cabinet	Not Applicable
No. of Faucets	3	3	3	3	3	3	2
Cold Water Storage Capacity (Ltrs)	3.2	3.2	3.2	3.2	3.2	8	3.2
Cooling Capacity (Ltrs/Hr)	3	3	2.5	3	3	6	3
Hot Water Storage Capacity (Ltrs)	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Unit Dimension (W X D X H) in mm	325x360x1000	310x345x490	310x345x940	310x345x940	310x345x940	320x380x980	330x427x495
Weight in Kg.	16.3	11.4	16.65	15.5	15.5	25.7	18.2
Refrigerant	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)	Non CFC (R134a)
Cabinet Capacity/Refrigerator Capacity	19/20	N/A	19/20	19/20	NA	NA	NA
Cooling Cabinet Temperature	NA	NA	≤12°C	NA	NA	NA	NA
Tap Function	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold	Hot (with child lock), Normal & Cold
Display	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators	LED Indicators
RO TDS	NA	NA	NA	NA	NA	less then 150ppm	less then 150ppm

A **TATA** Product

VOLTAS



VOLTAS | COMMERCIAL REFRIGERATION

Voltas 24x7 Customer Service - 1860 599 4555, 9650694555.
For product registration SMS <WTA> to 9289525321.
Buy only genuine Voltas stabilizers.

Visit us at www.myvoltas.com
To locate your nearest store,
log on to: www.myvoltas.com/store-locator

Follow us at  My Voltas  My Voltas  My Voltas
in Voltas Limited  My Voltas

CORPORATE HEAD OFFICE: Voltas Limited, Voltas House A, Dr. Babasaheb Ambedkar Road, Chinchpokli, Mumbai - 400033. Phone: 022-66656666. **BRANCHES:** **DELHI:** Voltas Limited, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi - 110044. Phone: 011-66505550. **HARYANA:** Voltas Limited, A - 43, Mohan Co-operative Industrial Estate, Mathura Road, New Delhi. Phone: 011-66505582. **GHAZIABAD:** Voltas Limited, D-15, R.S. Plaza, 3rd Floor, Raj Nagar, RDC, Ghaziabad - 201001. Ph. 0120-6404801. **CHANDIGARH:** Voltas Limited, Plot No. 194-195, First Floor, Industrial Area Phase-2, Chandigarh - 160002. Phone: 0172-4111800. **LUCKNOW:** Voltas Limited, Shalimar Titanium, Block - C, 4th floor, Office Nos. 410 - 412, Plot No. TCG -1/1, Opp. Indira Gandhi Pratishthan, Vibhuti Khand, Gomti Nagar, Lucknow - 226 010. Phone: 0522-6566961. **JAIPUR:** Voltas Limited, Diamond Tower, 201-203, Purani Chungi, Ajmer Road, Jaipur-302021. Phone: 0141-2972015. **HYDERABAD:** Voltas Limited, 7-2-1735, Sanath Nagar, Hyderabad-500018. Phone: 040-66743001. **VIJAYAWADA:** Voltas Limited, #23-2-7, Bhagat Singh Road, Next to Naadars Function Hall, Satyanarayanaapuram, Vijayawada - 520011. For institutional Enquiry - 8186052052. **BANGALORE:** Voltas Limited, 7th Floor, 701- Pride Hulkul 116, Lalbagh Road, Bangalore-560027. Phone: 08022535600. **CHENNAI:** Voltas Limited, No. 624, Anna Salai, Chennai - 600018. Phone: 66760333/11. **KOCHI:** Voltas Limited, Ambanath building, 39/3522, M.G. Road, Ravipuram, Kochi-682016. Phone: 0484-6605555. **COIMBATORE:** Voltas Limited, 1413, Trichy Road, Coimbatore - 641018. Phone: 0422-6502419/6530080. **MUMBAI:** Voltas Limited, Voltas House B, 2nd Floor, T.B. Kadam Marg, Chinchpokli, Mumbai - 400033. Phone: 022-66656333. **PUNE:** Voltas Limited, Equitorial Forum, 2nd & 3rd Floor, Mumbai-Pune Road, Wakadewadi, Pune - 411003. Phone: 020-66011776. **THANE:** Voltas Limited, Unit II, 1st Floor, 2nd Pokhran Road, Thane-400601. Phone: 022-67920106/07. **NAGPUR:** Adisun Trade Center, 5th Floor, Plot No. 38, Dhaga Layout, Near Crazy Castel, Nagpur - 440010. Phone: 9823036896. **AHMEDABAD:** Voltas Limited, A-301, Shivalik Corporate Park, Shivranjini Crossroad Satellite, Ahmedabad-380015. Phone: 0790-66301190/91. **INDORE:** 501-B, 5th floor, NRK Business Park, Block B-1, PU-4, Sch.no.54 Vijay Nagar Square, A.B.Road, Indore-452010, M.P. Phone: 0731-4043512 & 40463933. **RAIPUR:** Voltas Limited, Kunwar Ben Karsam Bhai Chamber, Shop No. 419/420, 4th Floor, New Timber Market, Mandi Market, Devendra Nagar, Raipur - 492001. Ph: 4033886. **KOLKATA:** Voltas Limited, Unit No. 805, 8th Floor, Godrej Waterside Tower - 2, Plot No. - 5, Block DP, Sector - V, Salt Lake, Kolkata - 700091. Phone: 033-66266200-205. For Institutional Inquiry - 9771491152. **PATNA:** Voltas Limited, Maharaja Complex, 305-A, 3rd Floor, Frazer Road, Patna-800001. For Institutional Inquiry - 7091091400 / 7707008948. **JAMSHEDPUR:** Voltas Limited, Voltas House, 3rd Floor, Main Road, Bistupur, Jamshedpur - 831001. Phone: 0657-6455921. For Institutional Inquiry - 9234509877 / 0657-6622378. **BHUBANESWAR:** Voltas Limited, B-15, 2nd Floor, Arthant Plaza, Shaheed Nagar, Bhubaneswar-751007. Phone: 0674 -2544919/18. For Institutional Inquiry - 09937140010. **GUWAHATI:** Voltas Limited, Upasana Palace Building, 6th Floor, Dr. Rajendra Prasad Road, Near Ganesh Mandir, Ganeshguni, Guwahati - 781006. For Institutional Inquiry - 9706982628.

© In India, E-Waste (Management and Handling) Rules 2016 & E-Waste Management Amendment Rules 2018 has been notified by the Ministry of Environment, Forests and Climate Change Government of India. Voltas Limited (Voltas) stands committed to implement E-Waste Rules. Voltas has done tie-up with the government authorised E-Waste Recycler for facilitating our Channel partners/customers to dispose and/or discard Electrical and Electronic Products after its end-of-life (when a product/part is non-operational or non-repairable) and including spare parts. The authorised recycler has expertise in assisting Voltas in fulfilling their compliances related to EPR and E-waste Management. Channel partners/customers need to get in touch with Voltas Call Centre (9650694555) to dispose and/or discard Electrical and Electronic Products after its end-of-life. Channel partners/Consumers should contribute to resource conservation and prevent potential environmental problems by a simple action - the proper depositing of their old consumer durable products, its accessories or defective spares with authorised recyclers. E-waste should be disposed of separately from the general waste stream via designated collection facilities identified by Voltas.

*Features are available in select models only. T & C apply. As a continuous policy of product innovations at Voltas, design and specifications are subject to change without prior notice.